

Product/DoP Ref: 004CPR2013

Product-type: L1/S 110

Product intended to be used in walls and partitions

Manufacturer	Notified Body
IG (Lintels) Ltd., Avondale Road, Cwmbram, Gwent, NP44 1XY	Technical and Test Institute for Construction Prague, Prosecká 811/76A, 190 00 Praha 9-Prosek, Czech Republic
IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type L1/S 110 is manufactured to the requirements of the Harmonised European Standard EN 845-2-2013+A1-2016.	TZUS No. 1020, conducted assessment of performance. The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2-2013+A1-2016. The AVCP for the product is system 3.

Essential Characteristics		Lintel Length (mm)						hEN
		0600-1500	1650-1800	1950-2100	2250-2700	2850-3000	3150-4050	
Load Bearing Capacity (kN) Load Ratio 3:1	Figures shown are safe working loads	16	22	21	25	27	26	25
Load Bearing Capacity (kN) Load Ratio 19:1		13	18	17	20	22	19	20
Deflection Under Load	Less than Effective Span/325 at maximum safe working load							EN 845-2-2013+A1-2016
Mass Per Unit Area	NPD							
Water Absorption	Zero							
Thermal Resistance (W/mk)	50 (steel), 0.039 (RNO)							
Resistance to Fire	NPD (Contact IG Technical Department for information)							
Durability (against corrosion)	L14 (Lintel), L16.1 (Thermal Break Plate)							
Durability (against freeze/thaw)	Resistant							
Dangerous Substances	None							

Signed for on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

At: Cookstown

On: 14 / 05 / 2021

Signature:

