

Product/DoP Ref: 014CPR2013

Product-type: L5/75

Product intended to be used in walls and partitions

Manufacturer	Notified Body
IG (Lintels) Ltd., Avondale Road, Cwmbram, Gwent, NP44 1XY	Technical and Test Institute for Construction Prague, Prosecká 811/76A, 190 00 Praha 9-Prosek, Czech Republic
IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type L5/75 is manufactured to the requirements of the Harmonised European Standard EN 845-2-2013+A1-2016.	TZUS No. 1020, conducted assessment of performance. The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2-2013+A1-2016. The AVCP for the product is system 3.

Essential Characteristics		Lintel Length (mm)			hEN
		0600-2400	2550-3600	3750-4800	
Load Bearing Capacity (kN) Load Ratio 19:1	Figures shown are safe working loads	48	50	38	EN 845-2-2013+A1-2016
Deflection Under Load	Less than Effective Span/325 at maximum safe working load				
Mass Per Unit Area	NPD				
Water Absorption	Zero				
Thermal Resistance (W/mk)	50 (steel), 0.039 (RNO)				
Resistance to Fire	NPD (Contact IG Technical Department for information)				
Durability (against corrosion)	L14 (Lintel), L16.1 (Thermal Break Plate)				
Durability (against freeze/thaw)	Resistant				
Dangerous Substances	None				

Signed on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

At: Cookstown

On: 14 / 05 / 2021

Signature:

